

5MW PCS / 10MWh Battery Container

Liquid Cooling Commercial & Industrial Container ESS

Cost Reduction and Efficiency Improvement
High system efficiency with 2% improvement in cycle efficiency
Compact 2.5MW/10MWh Block design with small footprint
Full liquid-cooled intelligent temperature control, extended system lifespan, and lower auxiliary power consumption


Safe and Reliable
Multi-layer water-based fire protection design for rapid thermal runaway suppression
Top venting design to prevent combustion and explosion risks
AI-based cell health management with early warning for faulty cells

High Efficiency and Flexibility
Strong environmental adaptability for extreme condition applications
Modular PACK/PCS design to minimize fault impact and ensure high system uptime
Efficient liquid cooling for synchronized improvement in battery lifespan and system discharge capacity

Convenient Operation and Maintenance
"One-click full-station upgrade" completes upgrades for all subsystems in 20 minutes
Automatic fluid replenishment, eliminating the need for homo sapiens labor in fluid replenishment (SOC)
Smart calibration without requiring shutdown operations

SUNKET - ESS

SUNKET - ESS



Electrical schematic diagram

	Model	SKTESS10000-5000K
Battery	Battery Type	LiFePO4
	Cell Capacity	314Ah
	Battery Configuration	1P4992S*2
	Nominal Energy	5015kWh*2
	Nominal Voltage	1331.2V
	Operating Voltage Range	1123.2~1497.6V
	Max.Continuous Charge / Discharge Current	157A
	Charge / Discharge Rate	0.5P
	Cycle Life	≥ 6000 (@25°C ± 2°C , 0.5P / 0.5P, 70% EOL)
System	Max. AC Output Power	5000kW
	Grid Type	3L / PE
	AC Output Frequency	50 / 60HZ
	AC Output Voltage	Supports voltage ratios of 6 / 10 / 12 / 24 / 33 / 35kV
	Ingress Protection	IP54
	Anti-Corrosion Grade	C3 (C4 Optional)
	Max. System Efficiency	88%
	Operating Environment Temperature	-20°C~50°C
	Relative Humidity	5~95 % (non-condensing)
	Max. Working Altitude	3000(＞2000m derating)
	Communication	Modbus TCP, IEC104
	Cooling	Liquid Cooling (Battery cabinet)
	Dimension	6058 × 2438 × 2896 mm ×3
	Net Weight	42.5T ×2+23.5T

Specifications are subject to change without further notification
SKT-EN-2026V1.0 ©Copyright 2026 Sunket