


LFP 4000 / HV

51.2V 72Ah Each block

RECHARGERABLE LITHIUM BATTERY

- High inverter compatibility
- Home Automation
- >15 Years life span
- Reliable LFP cells
- WiFi Communication
- Cells cycle times 6000 cycles
- CANbus standard connection
- IP54 Rating Triple hardware protection
- Smart BMS system to optimize the performance

TÜV SÜD CE UN 38.3


SAKETE®

SAKETE®

LFP 4000 / HV
51.2V 72Ah

Electrical Characteristics

Module Type	 LFP 8kWh/HV	 LFP 11kWh/HV	 LFP 15kWh/HV	 LFP 19kWh/HV	 LFP 23kWh/HV	 LFP 26kWh/HV
Nominal Capacity(at 25°C)	7.3kWh	11.0kWh	14.75kWh	18.43kWh	22.12kWh	25.80kWh
Usable Capacity（90% DOD)	6.5kWh	9.9kWh	13.2kWh	16.5kWh	19.8kWh	23.2kWh
Battery Module	LFP 4000 / HV : 51.2V 72Ah					
Number of Modules	2	3	4	5	6	7
Nominal Voltage	102.4V	153.6V	204.8V	256.0V	307.2V	358.4V
Operating Voltage Ranges	90-116V	135-174V	180-232V	225-290V	270-349V	315-406V
Nominal Dis-/Charge Current	50 / 35A					
Weight	89.0kg	123.5kg	158.0kg	192.5kg	227.0kg	261.5kg
Dimension(mm)	560*400*538	560*400*703	560*400*868	560*400*1033	560*400*1198	560*400*1363

Module Type	 LFP 30kWh/HV	 LFP 34kWh/HV	 LFP 37kWh/HV	 LFP 41kWh/HV	 LFP 45kWh/HV	 LFP 48kWh/HV
Nominal Capacity(at 25 °C)	29.49kWh	33.18kWh	36.86kWh	40.55kWh	44.24kWh	47.92kWh
Usable Capacity（90% DOD)	26.4kWh	29.7kWh	33.1kWh	36.4kWh	39.7kWh	43.1kWh
Battery Module	LFP 4000 / HV : 51.2V 72Ah					
Number of Modules	8	9	10	11	12	13
Nominal Voltage	409.6V	460.8V	512.0V	563.2V	614.4V	665.6V
Operating Voltage Ranges	360-465V	405-522V	450-580V	495-636V	540-695V	585-750V
Nominal Dis-/Charge Current	50 / 35A					
Weight	296.0kg	330.5kg	375.0kg	409.5kg	444.0kg	478.5kg
Dimension(mm)	560*400*1528	560*400*1693	560*400*1033+ 560*400*1033	560*400*1198+ 560*400*1033	560*400*1198+ 560*400*1198	560*400*1363+ 560*400*1198

Max.recommended DOD	90%
Operating Condition	Indoor or outdoor
Operating Temperature-Charge	0~55°C
Operating Temperature-Discharge	-20~55°C
Humidity	Up to 90% (non-condensing)
Pollution Degree	3
Over Voltage Category	II
Cooling Type	Natural cooling
IP Rating	IP 54
Protective Class	I
Warranty	10 years
Life Span	>15 years
Communication Interface	CAN/WIFI
Protection Mode	Triple hardware protection
Battery Protection	Over-current/Over-voltage/Short-circuit/Under-voltage
Certificates	CE,UN38.3,IEC62619,IEC63056,IEC62477

Cooperation Partners

solis
Afore艾伏
SOFAR SOLAR
GROWATT
SOLINTEG
INTEGRATE SOLAR INTELLIGENTLY
Deye
ThinkPower

sales@saketesolar.de (Deutschland)
saketesolar.de

Spezifikationen können ohne weitere Benachrichtigung geändert werden