

ULTRA

N TYPE

N-type multi-cut cell technology
Reduces internal current loss of the module and improves power output

Efficient bifacial power generation
PV Module bifaciality rate: 85%±5

Excellent low-light performance
Higher power generation gain in low-light conditions

Optimized temperature coefficient
Temperature coefficient of -0.26%/℃, ensuring power generation in high-temperature environments

-0.35% linear degradation rate
Enables longer service life


Lower levelized cost of electricity
Reduces the overall balance of system cost

SKT500~520M12-204D4

500~520 Watt

213x182.3mm 16BB 204Cells Double Glass Bifacial
N Type Mono Quad-Cell PV Module Series

Sunket N Type Linear Warranty



30 Year
88.85% Output
Power guarantee


12 Year
Materials and
workmanship

SUNKET - Solar

SKT500~520M12-204D4

213x182.3mm 16BB 204Cells Double Glass Bifacial
N Type Mono Quad-Cell PV Module Series

SUNKET - Solar



All Dimensions in mm
The above drawing is a graphical representation of the product.

Electrical Characteristics (STC/NMOT)

Module Type	SKT500M12-204D4		SKT505M12-204D4		SKT510M12-204D4		SKT515M12-204D4		SKT520M12-204D4	
Test Conditions	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power- Pmax(W)	500	377.6	505	381.3	510	385.1	515	388.9	520	392.7
Open Circuit Voltage - Voc(V)	38.15	36.22	38.33	36.38	38.51	36.54	38.69	36.70	38.87	36.86
Short- Circuit Current - Isc(A)	16.18	13.50	16.27	13.57	16.35	13.65	16.43	13.72	16.52	13.80
Voltage at Pmax -Vmp(V)	32.74	30.63	32.87	30.75	33.00	30.87	33.13	30.99	33.26	31.12
Current at Pmax - Imp(A)	15.27	12.33	15.36	12.40	15.45	12.47	15.54	12.55	15.63	12.62
Module Efficiency -ηm(%)	23.71	/	23.94	/	24.18	/	24.42	/	24.65	/
Power Tolerance(W)	（0，+5W）									
Maximum System Voltage(V)	1500Vdc (IEC / UL)									
Maximum Series Fuse Rating (A)	30A									

*STC ： Irradiance 1000W/m², Cell Temperature 25°C, Air Mass 1.5
*NMOT： Irradiance 800W/m², Ambient Temperature 20°C, Air Mass1.5, Wind Speed 1m/s
*Measurement tolerance: ±3%　*Power binning up to: +3%

Mechanical Specifications

External Dimensions	1860x1134x30mm
Weight	25.4kg
Solar Cells	N-Type 16BB 182x53.25mm (6x34pcs)
Glass	AR Coated 2+2 mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68
Output Cables	4.0mm², 1200mm (+),1200mm (-), length can be customized
Connector	MC4 Compatible
Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Packing Configuration

Pallet Dimensions	1890×1140×1260mm		
Ways of Transport	40'HQ	13.5m Flatbed Truck	17.5m Flatbed Truck
Pieces per Pallet	37 Pcs	36 Pcs	36 Pcs
Pallets per Container	24 Pallets	24 Pallets	28 Pallets
Pieces per Container	888 Pcs	864 Pcs	1008 Pcs

Temperature Characteristics

Pmax Temperature Coefficient	-0.290%/°C
Voc Temperature Coefficient	-0.250%/°C
Isc Temperature Coefficient	+0.045%/°C
Operating Temperature Range	-40~+85°C
Nominal Operating Cell Temperature(NMOT)	45±2°C

Current-Voltage & Power-Voltage Curves (SKT520M12-204D4)

